

# Material Safety Data Sheet

(Complies with 29 CFR 1910.1200)

<b>Section I</b>			
Manufacturer	Carlisle Brake and Friction 920 Lake Road Medina, Ohio 44256		
Emergency Phone .	330-725-4941	Effective Date	January 30, 2006
Chemical Name	Organic Material	Revision Date	10-25-12
Tradename	Organic Material		
Category	7359		

<b>Section II - Hazardous Ingredients / Identity</b>				
Component	OSHA-PEL (mg/m <sup>3</sup> )	ACGIH-TLV (mg/m <sup>3</sup> )	%	CAS No.
Teflon			Proprietary	2506-11-2
Carbon	Total=15.0 Resp.= 5.0	10.0	Proprietary	7782-42-5

<b>Section III - Physical Characteristics</b>			
Boiling Point	N/A		
Vapor Press (mm Hg)	N/A	Solubility in Water	N/A
Reactivity in Water	N/A	Vapor Density (Air=1)	N/A
Melting Point	N/A	Color	Gray
Appearance/Odor			

<b>Section IV - Fire and Explosion Data</b>			
Flashpoint	N/A	Method used	N/A
Flammable Limits (LEL/UEL)	N/A	Special Fire Fighting Procedure	None
Auto Ignition Temperature	N/A	Extinguishing Media	Water, CO <sub>2</sub> , dry chemical, chemical foam.
Unusual Fire and Explosion Hazards	None Know		
Wear self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode when fighting fires.			

<b>Section V - Reactivity Data</b>	
Stability	Stable
Incompatibility ( Materials to Avoid)	N/A
Hazardous Decomposition Products	N/A
Hazardous Polymerization	N/A
Conditions to Avoid	N/A

## Section VI - Health Hazards

### Effects of Overexposure:

Inhalation: No specific intervention is indicated as the compound is not likely to be hazardous by inhalation. Consult a physician if necessary. If exposed to fumes from overheating or combustion, move to fresh air. Consult a physician if symptoms persist.

Eyes: In case of contact, immediately flush with plenty of water for at least 15 minutes. Call a physician.

Skin: Not likely to be hazardous by skin contact, but cleansins the skin after use is advisable.

### Emergency Procedures

Eye Contact: Flush with clean water for 15 minutes. If irritation persists, contact a physician.

Skin Contact: Wash thoroughly with soap and water. If irritation persists, contact a physician.

Inhalation: Following exposure to a large amount of dust, remove from exposure. If breathing has stopped, perform artificial respiration. Contact a physician.

Ingestion: N/A

## Section VII - Spill/Leak Procedures

Handling, Storage	None applicable
DOT Shipping Rules	N/A
Spill/Leak	Steps to be taken if material is released or spilled: Sweep up or pick up all loose material.
Waste Disposal Methods	Landfill or incinerate in accordance with Federal, State and local regulations.

## Section VIII - Special Protection /Control Measures

Respiratory Protection/Ventilation	Use a NIOSH approved respirator with appropriate filters.
Protective Gloves	Wear gloves to avoid skin contact.
Eye Protection	Wear safety glasses or goggles.
Other Protective Equipment	N/A

## Section IX - Special Precautions

No special precautions necessary

### Disclaimer

The information contained herein is based on data available at this time and is believed to be accurate. No warranty, however, is expressed or implied in no event will Carlisle Brake and Friction be liable for incidental or consequential damages of any kind regarding the accuracy of this data or the results to be obtained from the use thereof. Since information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, no responsibility is assumed for the results of its use. The person receiving this information should make his own determination of the suitability of the material for his particular purpose.